SAFETY DATA SHEET

1. Identification

Product identifier	KD118D KNOCK DOWN TOTAL HOME & INDOOR GARDEN INSECT KILLER	
Other means of identification		
Product code	KD118D	
Recommended use	Pesticide	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	blier/Distributor information	
Manufacturer		
Company name	KUUS INC.	
Address	450 TAPSCOTT ROAD	
	SCARBOROUGH, ON M1B 1Y4	
	Canada	
Telephone	General Assistance	1-416-298-7724
E-mail	Not available.	
Emergency phone number	Canutec	1-888-226-8832
		1-613-996-6666

2. Hazard(s) identification

Physical hazards Health hazards Label elements	Flammable aerosols Not classified.	Category 1
Signal word	Danger	
Hazard statement	Extremely flammable aerosol.	
Precautionary statement		
Prevention		pen flames and other ignition sources. No smoking. In source. Do not pierce or burn, even after use.
Response	Not available.	
Storage	Protect from sunlight. Do not expose to tempe	eratures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
Other hazards	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	15 - 40
Distillates (petroleum), Hydrotreated Light		64742-47-8	7 - 13
Propane		74-98-6	3 - 7

Chemical name	Common name and synonyms	CAS number	%
Piperonyl Butoxide		51-03-6	1 - 5
Pyrethrins		8003-34-7	0.1 - 1
Other components below repo	rtable levels		40 - 70
All concentrations are in percent b	by weight unless ingredient is a gas. Gas concer	ntrations are in percent by vol	lume.
4. First-aid measures			
Inhalation	If symptoms develop move victim to fresh air.	Get medical attention if sym	ptoms persist.
Skin contact	Wash off with soap and water. Get medical at	ttention if irritation develops a	and persists.
Eye contact	Rinse with water. Get medical attention if irrita	ation develops and persists.	
Ingestion	In the unlikely event of swallowing contact a p	ohysician or poison control ce	enter.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporar	y irritation.	
Indication of immediate medical attention and special treatment needed	Treat symptomatically.		
General information	Ensure that medical personnel are aware of the protect themselves.	he material(s) involved, and t	ake precautions to
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	on dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized contair During fire, gases hazardous to health may be		ed to heat or flame
Special protective equipment and precautions for firefighters	Firefighters must use standard protective eque face shield, gloves, rubber boots, and in enclosed in the statement of the sta		dant coat, helmet w
Fire fighting equipment/instructions	Move containers from fire area if you can do water to prevent vapor pressure build up. For holder or monitor nozzles, if possible. If not, w	r massive fire in cargo area,	use unmanned hos
Specific methods	Use standard firefighting procedures and con containers from fire area if you can do so with breathe fumes.		

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of

8. Exposure controls/personal protection

the SDS).

US. ACGIH Threshold Limit Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Alberta OELs (Occ	upational Health & Safety Code, Scl	hedule 1, Table 2)	
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Safety Regulation 296/97, as	-		-
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
	eg. 217/2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Ontario OELs. (Cor	ntrol of Exposure to Biological or Cl	hemical Agents)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	TWA	800 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Quebec OELs. (Mir	nistry of Labor - Regulation Respect	ting the Quality of the Work Er	nvironment)
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
logical limit values	No biological exposure limits noted	for the ingredient(s).	
osure guidelines			
Canada - British Columbia (DELs: Skin designation		
Distillates (petroleum), H	-	be absorbed through the skin.	
64742-47-8)	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
propriate engineering	should be matched to conditions. If or other engineering controls to mai	applicable, use process enclosu ntain airborne levels below reco	mmended exposure limits.
propriate engineering trols	should be matched to conditions. If or other engineering controls to mai	applicable, use process enclosu ntain airborne levels below reco plished, maintain airborne levels	mmended exposure limits. I

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear suitable protective clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	149.18 °F (65.1 °C) estimated
Flash point	-99.4 °F (-73.0 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	4.9 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	40.83 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	610.52 °F (321.4 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Heat of combustion (NFPA 30B)	17.02 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.838 estimated
VOC (Weight %)	0.59 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Distillates (petroleum), Hydr	otreated Light (CAS 64742-47-8)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Isobutane (CAS 75-28-5)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Piperonyl Butoxide (CAS 51	-03-6)	
Acute		
Dermal		
LD50	-	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5.2 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

Components	Species	Test Results
	Rat	1355 mg/l
		658 mg/l/4h
* Estimates for product may b	be based on additional compo	onent data not shown.
Skin corrosion/irritation	Prolonged skin contact ma	ay cause temporary irritation.
Serious eye damage/eye rritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitizatio	n	
Canada - British Columbia	OELs: Respiratory or skin s	sensitiser
Pyrethrins (CAS 8003-34	4-7) Capable of causing respiratory, dermal or conjunctival sensitization.	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity		
ACGIH Carcinogens		
Pyrethrins (CAS 8003-34	4-7)	A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: c	arcinogenicity	
PYRETHRUM (CAS 800		Not classifiable as a human carcinogen.
IARC Monographs. Overall	•	-
Piperonyl Butoxide (CAS		3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	· · ·	ed to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
12. Ecological information	n	
Ecotoxicity	Very toxic to aquatic life w	ith long lasting effects.
Components	Species	Test Results

Distillates (petroleum)	, Hydrotreated Ligh	t (CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Piperonyl Butoxide (C	AS 51-03-6)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.0027 - 0.0043 mg/l, 96 hours
Pyrethrins (CAS 8003	-34-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia)	0.018 - 0.032 mg/l, 48 hours
Fish	LC50	Brown trout (Salmo trutta)	0.0165 - 0.0229 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)		
Isobutane		2.76
Piperonyl Butoxide		4.75
Propane		2.36
Mobility in soil	No data available.	

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation
potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG			
UN number	UN1950		
UN proper shipping name	AEROSOLS, flammable		
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Packing group	Not applicable.		
Environmental hazards	Yes		
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.			
This product meets the exemption requirements and may be shipped as a limited quantity.			
ΙΑΤΑ			

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention Not applicable.

Kyoto protocol

Not applicable. Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or regi	on Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Subs (PICCS)	No No
United States & Pu	erto Rico Toxic Substances Control Act (TSCA) Inventory	Yes
	at all components of this product comply with the inventory requirements ad one or more components of the product are not listed or exempt from listing	, , , , , , , , , , , , , , , , , , , ,
Issue date	06-06-2019	
Version #	02	
Disclaimer	The information provided in this Safety Data Sheet is information and belief at the date of its publication. Th guidance for safe handling, use, processing, storage,	e information given is designed only as a transportation, disposal and release and is

Revision information

materials or in any process, unless specified in the text. Product and Company Identification: Alternate Trade Names

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other