SAFETY DATA SHEET

1. Identification

Product identifier KD300C KNOCK DOWN X-MAX FLYING INSECT KILLER

Other means of identification

Product code KD300C
Recommended use Pesticide
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name KUUS INC.

Address 450 TAPSCOTT ROAD

SCARBOROUGH, ON M1B 1Y4

Canada

Telephone General Assistance 1-416-298-7724

E-mail Not available.

Emergency phone number Canutec 1-888-226-8832

1-613-996-6666

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsAcute toxicity, inhalationCategory 4Aspiration hazardCategory 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Harmful if inhaled.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Avoid breathing gas. Use only outdoors or in a well-ventilated area.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF

INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	40 - 70

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), Heavy Alkylate		64741-65-7	7 - 13
Piperonyl Butoxide		51-03-6	7 - 13
Propane		74-98-6	7 - 13
Distillates (petroleum), Hydrotreated Light		64742-47-8	5 - 10
Pyrethrins		8003-34-7	1 - 5
Other components below reportab	e levels		0.5 - 1.5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Aspiration may cause pulmonary edema and pneumonitis.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

Water spray. Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH	Threshold	Limit	Values
------------------	------------------	-------	---------------

Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Sc	hedule 1, Table 2)	
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. British Columbia OELs. (6 Safety Regulation 296/97, as amen		s for Chemical Substances, C	ccupational Health and
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Manitoba OELs (Reg. 217)	/2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Ontario OELs. (Control of	Exposure to Biological or C	hemical Agents)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	TWA	800 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Quebec OELs. (Ministry o	f Labor - Regulation Respec	ting the Quality of the Work E	nvironment)
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	
		!!	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - British Columbia OELs: Skin designation

TWA

64742-47-8)

Pyrethrins (CAS 8003-34-7)

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

5 mg/m3

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing considerations after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state
Form
Color
Not available.

Odor
Not available.

Odor threshold
Not available.

PH
Not available.

Melting point/freezing point
Not available.

Initial boiling point and boiling

range

2.59 °F (-16.34 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

1 % estimated

(%)

Flammability limit - upper

(%)

7 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 803.01 °F (428.34 °C) estimated

Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Heat of combustion (NFPA 40.

40.55 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Specific gravity 0.525 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials
Hazardous decomposition

products

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Components Species Test Results

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute Dermal

LD50

Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat

> 7.5 mg/l, 6 Hours

> 4.6 mg/l, 4 Hours

Oral

LD50 Rat

> 5000 mg/kg

Isobutane (CAS 75-28-5)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

Piperonyl Butoxide (CAS 51-03-6)

Acute

Dermal

LD50 - > 2000 mg/kg

Inhalation

LC50 Rat > 5.2 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

Components Species Test Results

658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Canada - British Columbia OELs: Respiratory or skin sensitiser

Pyrethrins (CAS 8003-34-7) Capable of causing respiratory, dermal or conjunctival

sensitization.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Pyrethrins (CAS 8003-34-7)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

PYRETHRUM (CAS 8003-34-7) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Piperonyl Butoxide (CAS 51-03-6)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results	
Distillates (petroleum)	, Hydrotreated Ligh	t (CAS 64742-47-8)		
Aquatic				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
Naphtha (petroleum),	Heavy Alkylate (CA	AS 64741-65-7)		
Aquatic				
Algae	IC50	Algae	30000 mg/L, 72 Hours	
Piperonyl Butoxide (C	AS 51-03-6)			
Aquatic				
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0.0027 - 0.0043 mg/l, 96 hours	
Pyrethrins (CAS 8003	-34-7)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia)	0.018 - 0.032 mg/l, 48 hours	

Brown trout (Salmo trutta)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Crustacea Fish

Partition coefficient n-octanol / water (log Kow)

LC50

Isobutane 2.76 Piperonyl Butoxide 4.75 0.0165 - 0.0229 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

Propane 2.36

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

TDG

UN1950 **UN** number

UN proper shipping name

AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not applicable.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN1950 **UN number**

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Environmental hazards Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN1950 **UN** number **UN proper shipping name AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s)

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes F-D. S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

No

Philippine Inventory of Chemicals and Chemical Substances

16. Other Information

Philippines

Issue date 06-06-2019

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).